




- ▶ Home
- ▶ What's New
- ▶ Press Release
- ▶ Hot Products
- ▶ Product Lines
- ▶ Sales
- ▶ Online Support
- ▶ Site Map
- ▶ TDK Links



PART #NLFC252018T-330K

Inductors, SMD Type, NLFC Series



SPECIFICATIONS:

Inductance	33 μ H
Inductance Tolerance	\pm 10%
Rated Current Max	0.085 A
DC Resistance Max	2.73 Ohm
Self Resonant Frequency Min	14 MHz
Operating Temperature Min	-20
Operating Temperature Max	85
Length	2.5
L X W Metric (Inch)	2520 (1008)
Lead Spacing	
Width	2 mm
Height	1.8
Diameter	
Thickness	1.8 mm

FEATURES:

- 1.This is a magnetic shielded type, best for the power supply line.
- 2.There is a series of 5 types from 2016 to 5650 type.

APPLICATIONS:

- Personal Computers
- HDDs
- Other electronic appliances

PACKAGING:

Ammo-Pack	NO
Bulk	NO
Tape Reel	YES

SOLDERING:

Flow	YES
Hand	YES
Reflow	YES

IMAGES:

- [Catalog Pages](#)
- [Data Sheet](#)
- [Z vs. Freq.](#)
- [L vs. Freq.](#)

[New Search](#)

Disclaimer:

TDK Corporation of America reserves the right to make changes in specifications at any time without notice. As the reader is cautioned to verify that the data sheet is current before placing orders.

[Home](#) || [What's New](#) || [Press Release](#) || [Hot Products](#) || [Components](#) || [Po](#)
|| [FA](#) || [Anechoic Chambers](#) || [Sales](#) || [Online Support](#) ||



Copyright © 1999-2002 TDK Corporation of America. All rights reserved.



[Privacy Statement](#)